

CMS Server



Introduction

CMS Server is a Content Management System server that allows you to upload media files, scrolling tickers or firmware to up to 1000 digital signage devices using a Web interface. You can also look up records and analysis of user and device activities.

Key Features

- Connection with up to 1000 PN300 / SQP133 / SQP110
- Web interface to remotely upload content, scrolling ticker, and schedule using Internet Explorer, Firefox, Google Chrome or Safari
- Remote device reboot and firmware upgrade
- Instant display of device status and information
- Support for Dynamic DNS
- Records and analysis of user and device activities

GV-USB Dongle

An USB dongle is required to connect CMS Server to devices. Starting from a minimum of 20 connections to a maximum of 1000 connections, different number of connections is available for purchase in increments of 5 connections.



USB Dongle

System Requirements

	500 Devices or Below	500 Devices or Above
OS	32-bit and 64-bit Windows 7 / XP / Vista / Server 2008	
CPU	Core Duo, 2.6 GHz	Core Duo, 3.0 GHz
Memory	1 GB	2 GB
Browser	* Internet Explorer 8.0 * Firefox 6.0.2 * Google Chrome 15.0.874.121 * Safari 5.1	
Hardware	External GV-USB Dongle	

Note: Specifications are subject to change without notice.